A alaga	Product Information	
A class	AHF771IX	
	MODEL	AHF771IX
	Energy efficiency classes of domestic range hoods (A-G)	Α
	Annual Energy Consumption - AEC hood (kWh/a)	60
	Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	Α
	Lighting Efficiency classes (A-G)	Α
	The Grease Filtering Efficiency classes (A-G)	D
	Sound power level L WA - (dB)	68
	Time increase factor - f	0.9
	Fluid Dynamic Efficiency - FDE hood	30.3
	Energy Efficiency Index - EEI hood	54.3
	Measured air flow rate at best efficiency point - Q BEP (m 3 /h)	420
	Measured air pressure at best efficiency point P BEP (Pa)	428.7
	Measured electric power input at best efficiency point - W BEP (W)	164.9
	Nominal power of the lighting system - W L (W)	8
	Average illumination of the lighting system on the cooking surface - E middle (lux)	700.6
	Lighting Efficiency LE hood - (lux/Watt)	87.58
	Gerase Filtering Efficiency GFE hood - (%)	74
	Minimum airflow (Q min )	462.6m <sup>3</sup> /h
	Maximum air flow - Q max (m 3 /h)	646m <sup>3</sup> /h
	Airflow -boost (Q boost )	723.6m <sup>3</sup> /h
	Minimum sound power level L WA - (dB)	56dB
	Maximum sound power level L WA - (dB)	68dB
	Sound power level-boost L WA - (dB) Measured	71dB
	power consumption off mode P o (W)	0.293
	Measured power consumption in standby mode - P s (W)	0.483
	Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "	